

In the Claims:

Claims 1 to 20 (canceled).

1 21. (previously presented) Deployable structure with a modular
2 configuration consisting of at least one collapsible module
3 (91), which is bounded by joints (114, 115, 126, 121) of a
4 first joint set, which are corner joints of the module (91)
5 and lie in a first surface, and by joints (101, 102, 113,
6 108) of a second joint set, which are corner joints of the
7 module (91) and lie in a second surface, and with at least
8 a first joint (109, 122) of a third joint set, which first
9 joint lies outside of the first surface and is not located
10 at a corner of the module, whereby at least some of the
11 joints of the first and second joint sets respectively have
12 a constrained and fixable position relative to one another
13 by being connected with one another by a guide mechanism
14 comprising scissors arrangements, characterized in that:

15 the first joint (109) of the third joint set is
16 connected respectively with at least two of the joints
17 (114, 115, 113, 121) selected from at least one of the
18 first and second joint sets by a respective tension-only
19 connecting element (39, 41, 43, 45) that is adapted and
20 able to transmit only tension forces,

21 said first joint (109) of the third joint set is
22 arranged below a lowermost joint (114, 115, 121) among the
23 joints of the first joint set with which said first joint
24 (109) of the third joint set is connected,

25 forces arising upon loading of the structure by at
26 least one of a useful working load and a self-weight load
27 are transmittable as tension forces away from said first
28 joint (109) of the third joint set to the joints (114, 115,
29 113, 121) of at least one of the first and second joint
30 sets via the tension-only connecting element (39, 41, 43,
31 45) that is adapted and able to transmit only tension
32 forces,

33 a second joint (122) of the third joint set is
34 connected with at least one joint (101, 102, 113, 108) of
35 the second joint set by a connecting element (40, 42,
36 44, 46) that transmits tension and compression forces, and

37 the first joint (109) of the third joint set is
38 connected with the second joint (122) of the third joint
39 set by a connecting element (11) that transmits compression
40 and tension forces..

Claims 22 to 24 (canceled).

1 25. (previously presented) Structure according to claim 21,
2 characterized in that at least one of the first surface and
3 the second surface is a respective plane.

1 26. (previously presented) Deployable structure with a modular
2 configuration consisting of at least one collapsible module
3 (91), which is bounded by joints (114, 115, 126, 121) of a
4 first joint set, which are corner joints of the module (91)
5 and lie in a first surface, and by joints (101, 102, 113,

4299/WFF:kd

- 3 -

108) of a second joint set, which are corner joints of the module (91) and lie in a second surface, and with at least one joint (109, 122) of a third joint set, which lies outside of the first surface, whereby at least some of the joints of the first and second joint sets respectively have a fixable position relative to one another by being connectable with one another by a guide mechanism, characterized in that, one of the joints (109) of the third joint set is connected respectively with at least two of the joints (114, 115, 113, 121) selected from at least one of the first and second joint sets by a respective tension-only connecting element (39, 41, 43, 45) that is adapted and able to transmit only tension forces, and said one of the joints of the third joint set is arranged below a lowermost joint (114, 115, 121) among the joints of the first joint set with which said one of the joints of the third joint set is connected, and characterized in that forces arising upon loading of the structure by at least one of a useful working load and a self-weight load are transmittable as tension forces away from said one of the joints (109) of the third joint set to the joints (114, 115, 113, 121) of at least one of the first and second joint sets via the tension-only connecting element (39, 41, 43, 45) that is adapted and able to transmit only tension forces, and further characterized in that all of the joints (101, 102, 113, 108) of the second joint set, and said one of the joints (109) of the third joint set, which is connected with said at least two joints (114, 115, 113,

4299/WFF:kd

- 4 -

34 121) selected from at least one of the first and second
35 joint sets by the tension-only connecting element (39, 41,
36 43, 45), lie in one plane.

Claim 27 (canceled).

1 28. (previously presented) Structure according to claim 21,
2 characterized in that the scissors arrangements of the
3 guide mechanism comprise guide means, and in that at least
4 one joint (114) of the first joint set of a first corner of
5 the module (91) arranged on an outer perimeter of the
6 structure is connected by the guide means with a joint
7 (102) of the second joint set of a first neighboring corner
8 of the module (91) opposite the first corner and arranged
9 on the outer perimeter of the structure, and a joint (101)
10 of the second joint set of a second corner is connected by
11 the guide means with a joint (115) of the first joint set
12 of a second neighboring corner opposite the second corner.

1 29. (previously presented) Structure according to claim 28,
2 characterized in that the guide means comprise connecting
3 elements (15, 16) that transmit tension and compression
4 forces and that are crossed-over and pivotally connected
5 with one another.

1 30. (previously presented) Structure according to claim 29,
2 characterized in that the connecting elements (16, 32, 17,
3 20, 34, 21, 24, 36, 25, 28, 38, 29) that transmit tension

4 and compression forces and that lead to supports of the
5 structure have a greater load capacity and a larger
6 diameter, than remaining ones of the connecting elements
7 (15, 31, 18, 19, 33, 22, 23, 35, 26, 27, 37, 30) of the
8 guide means.

1 31. (previously presented) Structure according to claim 29,
2 characterized in that at least a portion of the connecting
3 elements (15, 16; 17, 18; up to 37, 38), which are
4 pair-wise crossed-over and pivotally connected with one
5 another and which transmit tension and compression forces,
6 are connected with one another offset from their center in
7 the longitudinal direction.

1 32. (previously presented) Structure according to claim 21,
2 characterized in that multiple modules (91, 92, 93, 94) are
3 arranged next to one another, and in that neighboring
4 modules comprise common joints.

1 33. (previously presented) Deployable structure with a modular
2 configuration consisting of at least one collapsible module
3 (91), which is bounded by joints (114, 115, 126, 121) of a
4 first joint set, which are corner joints of the module (91)
5 and lie in a first surface, and by joints (101, 102, 113,
6 108) of a second joint set, which are corner joints of the
7 module (91) and lie in a second surface, and with at least
8 one joint (109, 122) of a third joint set, which joint lies
9 outside of the first surface and is not located at a corner

4299/WFF:kd

- 6 -

10 of the module, whereby at least some of the joints of the
11 first and second joint sets respectively have a constrained
12 and fixable position relative to one another by being
13 connected with one another by a guide mechanism comprising
14 scissors arrangements, characterized in that, one of the
15 joints (109) of the third joint set is connected
16 respectively with at least two of the joints (114, 115,
17 113, 121) selected from at least one of the first and
18 second joint sets by a respective tension-only connecting
19 element (39, 41, 43, 45) that is adapted and able to
20 transmit only tension forces, and said one of the joints of
21 the third joint set is arranged below a lowermost joint
22 (114, 115, 121) among the joints of the first joint set
23 with which said one of the joints of the third joint set is
24 connected, and characterized in that forces arising upon
25 loading of the structure by at least one of a useful
26 working load and a self-weight load are transmittable as
27 tension forces away from said one of the joints (109) of
28 the third joint set to the joints (114, 115, 113, 121) of
29 at least one of the first and second joint sets via the
30 tension-only connecting element (39, 41, 43, 45) that is
31 adapted and able to transmit only tension forces, and
32 characterized in that the expansion of the module (91) or
33 the structure (90) is adjustable by an operating
34 arrangement.

1 34. (previously presented) Structure according to claim 33,
2 characterized in that the operating arrangement comprises

4299/WFF:kd

- 7 -

3 expansion and retraction mechanisms including an expansion
4 cable and a retraction cable, which are guided in the
5 respective joints over deflection mechanisms and are
6 fixably operable on a common joint (101).

1 35. (previously presented) Structure according to claim 34,
2 characterized in that the expansion cable (1) is guided in
3 the respective joints over deflection mechanisms including
4 deflection rollers or deflection saddles, with at least two
5 different deflection radii.

1 36. (previously presented) Structure according to claim 34,
2 characterized in that the structure (90) can have a
3 pre-stress applied thereto by means of the operating
4 arrangement, and thereby the structure (90) takes on a
5 prescribable form in a loaded condition.

1 37. (previously presented) Structure according to claim 21,
2 characterized in that at least some of the joints selected
3 from at least one of the first joint set (114 to 121, 126),
4 the second joint set (101 to 108, 113), and the third joint
5 set (109 to 112, 122 to 125) are connectable by a membrane
6 in such a manner so that thereby an at least partially
7 closed outer surface of the first or second surface is
8 formed.

1 38. (previously presented) Structure according to claim 21,
2 characterized in that at least a portion of the joints (114

3 to 121, 126) of the first joint set and at least a portion
4 of the joints (122 to 125) of the third joint set are
5 connectable with at least one triangular panel element (201
6 to 216) in such a manner so that thereby an at least
7 partially closed outer surface of the first surface is
8 formed.

1 39. (previously presented) Structure according to claim 21,
2 characterized in that the connecting elements that transmit
3 tension and compression forces are articulately joined on
4 the respective joints and are formed by rods of aluminum.

1 40. (previously presented) Deployable structure with a modular
2 configuration consisting of at least one collapsible module
3 (91), which is bounded by joints (114, 115, 126, 121) of a
4 first joint set, which are corner joints of the module (91)
5 and lie in a first surface, and by joints (101, 102, 113,
6 108) of a second joint set, which are corner joints of the
7 module (91) and lie in a second surface, and with at least
8 one joint (109, 122) of a third joint set, which lies
9 outside of the first surface, whereby at least some of the
10 joints of the first and second joint sets respectively have
11 a fixable position relative to one another by being
12 connectable with one another by a guide mechanism,
13 characterized in that, one of the joints (109) of the third
14 joint set is connected respectively with at least two of
15 the joints (114, 115, 113, 121) selected from at least one
16 of the first and second joint sets by a respective

tension-only connecting element (39, 41, 43, 45) that is adapted and able to transmit only tension forces, and said one of the joints of the third joint set is arranged below a lowermost joint (114, 115, 121) among the joints of the first joint set with which said one of the joints of the third joint set is connected, and characterized in that forces arising upon loading of the structure by at least one of a useful working load and a self-weight load are transmittable as tension forces away from said one of the joints (109) of the third joint set to the joints (114, 115, 113, 121) of at least one of the first and second joint sets via the tension-only connecting element (39, 41, 43, 45) that is adapted and able to transmit only tension forces, and further characterized in that the tension-only connecting elements that are adapted and able to transmit only tension forces are attached by being articulately joined on the respective joints, and at least partially are formed by respectively two parallel extending wires or cables of steel.

41. (previously presented) Deployable structure with a modular configuration consisting of at least one collapsible module (91), which is bounded by joints (114, 115, 126, 121) of a first joint set, which are corner joints of the module (91) and lie in a first surface, and by joints (101, 102, 113, 108) of a second joint set, which are corner joints of the module (91) and lie in a second surface, and with at least one joint (109, 122) of a third joint set, which joint lies

4299/WFF:kd

- 10 -

9 outside of the first surface and is not located at a corner
10 of the module, whereby at least some of the joints of the
11 first and second joint sets respectively have a constrained
12 and fixable position relative to one another by being
13 connected with one another by a guide mechanism comprising
14 scissors arrangements, characterized in that, one of the
15 joints (109) of the third joint set is connected
16 respectively with at least two of the joints (114, 115,
17 113, 121) selected from at least one of the first and
18 second joint sets by a respective tension-only connecting
19 element (39, 41, 43, 45) that is adapted and able to
20 transmit only tension forces, and said one of the joints of
21 the third joint set is arranged below a lowermost joint
22 (114, 115, 121) among the joints of the first joint set
23 with which said one of the joints of the third joint set is
24 connected, and characterized in that forces arising upon
25 loading of the structure by at least one of a useful
26 working load and a self-weight load are transmittable as
27 tension forces away from said one of the joints (109) of
28 the third joint set to the joints (114, 115, 113, 121) of
29 at least one of the first and second joint sets via the
30 tension-only connecting element (39, 41, 43, 45) that is
31 adapted and able to transmit only tension forces, wherein
32 each said tension-only connecting element comprises at
33 least one wire or cable that is adapted and able to
34 transmit only tension forces.

Claims 42 to 48 (canceled).

4299/WFF:kd

- 11 -